

4T SUPER BIKE OIL



SAE Viscosity Grade: 10W/50

Performance Level: JASO MA2, API: SL

Product Description:

Extra high performance engine oil offering exceptional performance level to satisfy the most demanding modern designs of diesel engines operating under all conditions. It provides effective protection against soot build-up in current high-output diesel engines designed to comply with low-emission standards including those equipped EGR. The product offers maximum protection against soot generation and high temperature deposits formation. It provides effective resistance against oxidation, corrosion and wear and maintains engine cleanliness.

Main Benefits:

- ❖ Superior protection against wear under high temperature & high rpm conditions.
- ❖ Excellent engine cleanliness and protection against ring sticking & piston deposits.
- ❖ Smoother wet clutch operation and longer transmission life.
- ❖ Effective engine parts protection against rust & corrosion.

Application:

Recommended for use in four-stroke motorcycles engines, gearboxes and clutches.

Physical Characteristics		Test Method		Typical Values
SAE Grade				10w/50
Specific Gravity @ 60/60 F		ASTM D-4052		0.8572
Kinematic Viscosity		ASTM D-445		
@ 40 °C, cSt				130.10
@ 100 °C, cSt				18.67
Viscosity Index		ASTM D-2270		162
Flash Point, COC, C		ASTM D-92		242
Pour Point, C		ASTM D-97		-36