



SHARLU PRIME

SAE Viscosity Grade **10W/40**

Performance Level **API: SL/CF**

ACEA A3/B3/B4 -04, MB 229.3, VW 502 00/505 00.

Product Description

Sharlu Prime is a synthetic multigrade motor oil designed to provide improved anti-wear, increased oxidation control, enhanced engine cleanliness, and effective protection against rust and corrosion.

It provides outstanding engine protection even at severe operating conditions.

Main Benefits

- Outstanding high temperature protection.
- High oxidation resistance & thermal stability.
- Excellent engine cleanliness.
- Superior viscosity retention.

Application

Sharlu Prime is recommended for use in naturally aspirated or turbo charged gasoline or diesel engines. It is specially designed for high output, high performance multivalve engines of passenger cars.

Physical Characteristics	Test Method	Typical Values
SAE Grade		10W/40
Specific Gravity @ 60/60 °F	ASTM D-4052	0.8670
K. Viscosity, cSt @ 40 °C	ASTM D-445	96.15
K. Viscosity, cSt @ 100 °C	ASTM D-445	14.10
Viscosity Index	ASTM D-2270	150
TBN mg KOH/g	ASTM D-2896	7.00
Flash Point, COC °C	ASTM D-92	226
Pour Point, °C	ASTM D-97	-27