



DATA SHEET

Sharlu Race

API Service Classification: SP

Performance Level: GF-6

Product Description:

Sharlu SP is a fully synthetic motor oil developed with highly oxidation stable synthetic base oil and a premium additive package for added performance required to meet the demands of modern engine technology.

Sharlu SP demonstrates higher levels of corrosion protection, oxidation stability, deposit control, and Sludge and varnish protection.

Main Benefits:

- ❖ Maximum protection against wear and corrosion.
- ❖ Optimum deposit, varnishes, sludge control at high temperatures.
- ❖ Excellent oxidation stability
- ❖ Emissions system compatibility

Application

Sharlu SP is ideal for use in fuel injection, turbocharged and supercharged petrol engines in all operating conditions and all the year round.

Physical Characteristics	Test Method	Typical Values	
		0W/20	5W/30
SAE Grade			
Specific Gravity @ 60/60 °F	ASTM D-4052	0.8470	0.8580
K. Viscosity, cSt @ 40 °C	ASTM D-445	44.54	59.98
K. Viscosity, cSt @ 100 °C	ASTM D-445	8.44	10.22
Viscosity Index	ASTM D-2270	170	159
TBN mg KOH/g	ASTM D-2896	7.20	7.20
Flash Point, COC °C	ASTM D-92	222	224
Pour Point, °C	ASTM D-97	-42	-39